

PRIMEL 500®

Acrylic Resin Based Curing Liquid Agent for Concrete, Mortar and Surface Hardeners

FIELD OF APPLICATION

Used for curing and enhancing the performance of SUFACEFIX applied substrates.

Used for curing of screed concrete and cast concretes.

PROPERTIES

Prevents generation of cracks by preventing rapid loss of water.

Prevents dusting by increasing the wear resistance of the surface.

Prevents frost cracks by increasing the water impermeability.

APPLICATION

Apply with brush or by spraying as two coats after completing SURFACEFIX application upon loss of gloss on cast concrete surfaces and upon removal formwork for concrete cast in formwork.

CONSUMPTION

200-250 g/m²

TECHNICAL DATA

Density, g/cm ³	~0,82
Flash Point, °C	88
Drying Time, min	~45

PACKAGING AND STORING

- Available in 10 litre plastic drums.
- 1 year from the date of manufacture if stored in unopened original package, under dry, frost free conditions.

RECOMMENDATION

- Recommended temperature range for application: +5 °C, +35 °C.
- Protected from frost.
- Wash all tools used with water after application.
- Hazardous for health when ingested.
- Keep out of reach of children.
- Store in tightly closed container.
- Avoid contact with eyes and skin.

- Consult us for your question related to all other application instructions and for your technical questions.

CERTIFICATE OF CONFORMITY



Above stated data obtained in lab conditions. Entegre will not be liable for any defect in product occurring by reason of events or conditions not within its control such as misuse, mishandling, improper storage or improper installation. Entegre reserves the right to revise the information contained herein without prior notice.

ENTEGRE HARÇ SANAYİ VE TİC. A.Ş.

Hüseyinli Köyü Beykoz Cad. No:222/4 34799 Çekmeköy/İSTANBUL T: 0216 434 50 96 F: 0216 434 50 31 www.entegreharc.com.tr