

TECHNICAL DATA SHEET

BOARDFIX

Plasterboard Adhesive

APPLICATION FIELDS

BOARDFIX is a gypsum based adhesive and designed to secure plasterboard to the wall.

FEATURES & BENEFITS

It is for interior applications.

Provides comfortable, easy and fast application.

BOARDFIX has high adherence and strength values thanks to special additives.

BOARDFIX is classified as non-combustible (A1) material.

SURFACE PREPARATION

Surface to be treated; mould oil, dust, paint and etc. materials must be removed.

Application surface should be prevented from humidity.

APPLICATION

Firstly, add water to the mixing bowl, then add the BOARDFIX (approximately 13 lt water for 25 kg bag) and mix until the lumps go away. Wait 5 minutes, and mix again to obtain a homogeneous mixture. The mixture has applied on back of plasterboard with a heap of 10 cm diameter by 30-40 cm intervals. Then, plasterboard has pushed to the wall with a balance.

TECHNICAL DATA

Compressive Strength, N/mm ²	≥ 6
Bond Strength, N/mm ²	≥ 3
Adhesion Strength, N/mm ²	≥ 0,4
Initial Setting Time, min	50

STORAGE

Store plaster products inside in a dry location. Stack plaster bags on pallets away from damp floors or walls. Long-term outdoor storage is not recommended. All gypsum plasters are susceptible to variable moisture conditions and aging that can produce variations in setting time and performance problems. Products have a six-month shelf life when stored as recommended.